



(For Autofab Use Only)

P.O. Number: \_\_\_\_\_

9" CENTER SECTION PART NUMBER CONSTRUCTION

3M - A - S - 35 - A - A - 389

I) Prefix For 3rd Member

II) Case Type

- A. Aluminum
- N. Nodular
- S. Stock (Rated for applications up to 600hp)

III) Differential

- A. Auburn (available in 28 & 31 spline )
- C. Trac-Loc ( available in 28 & 31 spline )
- L. Detroit Locker ( available in 28, 31 & 35 spline )
- S. Steel Spool ( available in 28, 31, 33, 35 & 40 spline )
- T. True-Trac ( available in 28 & 31 spline )
- U. Aluminum Spool ( available in 28, 31, 35 & 40 spline )\*

\*40 spline Aluminum Spool must be used with Aluminum Case.

IV) Spline

28 - 31 - 33 - 35 - 40

V) Pinion Yoke

- A. 1350 Series
- B. 1310 Series
- C. Pinion Coupler
- D. 1350 Series (Aluminum)

VI) Pinion Support

- A. Aluminum Daytona Pro/ Street
- N. Nodular Daytona Pro /Street
- P. Aluminum Pro (35 spline pinion)
- T. 10-Hole Aluminum Pro Support (35 spline pinion - for use with Aluminum case)

VII) Gear Ratio

**PRO/STREET**

|     |     |     |
|-----|-----|-----|
| 300 | 471 | 600 |
| 325 | 486 | 614 |
| 350 | 500 | 620 |
| 370 | 514 | 633 |
| 389 | 529 | 650 |
| 411 | 543 | 700 |
| 430 | 567 |     |
| 457 | 583 |     |

**PRO/COMPETITION - DRAG RACING ONLY!**

|                  |                  |
|------------------|------------------|
| 350P \           | 486PS \          |
| 370P \           | 500P \           |
| 389P \           | 514P \           |
| 411P \ 35 Spline | 543P > 28 Spline |
| 429P / Pinion    | 600P / Pinion    |
| 457P /           | 620P /           |
| 471P /           | 650P /           |
| 486P /           |                  |

**SHIPPING ADDRESS**

Name \_\_\_\_\_  
 Address \_\_\_\_\_  
 City, State, Zip \_\_\_\_\_  
 Phone No. \_\_\_\_\_

**Phone - 410 796 8777**  
**Fax - 410 796 2006**

7443 Washington Blvd.  
Elkridge, MD, 21075